

Download File PDF Mazda 5 Workshop Manual

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

TECHNICAL DATA	
ENGINE TECHNICAL DATA	
Item	Specification
OCV coil resistance	6.9-7.3 ohms (30°C (86°F))
Maximum distortion, head gasket side of the cylinder head	0.06 mm (0.002 in)
Maximum distortion, manifold side	IN: 0.10 mm (0.0039 in) EX: 0.05 mm (0.002 in)
Maximum cutting length, manifold side	IN: Cutting not authorized EX: 0.20 mm (0.0079 in)
Standard valve seat contact width	1.41 mm (0.0555 in)
Valve seat angle	45°
Standard valve seat sinkage amount (Dimension L)	IN: 48.70-50.27 mm (1.919-1.979 in) EX: 48.70-50.27 mm (1.919-1.979 in)
Standard valve head margin thickness	IN: 1.70-1.95 mm (0.0669-0.0768 in) EX: 1.60-1.85 mm (0.0630-0.0728 in)
Standard valve length	IN: 106.55-107.15 mm (4.1949-4.2146 in) EX: 106.55-117.15 mm (4.1886-4.6122 in)
Minimum valve length	IN: 106.33 mm (4.1862 in) EX: 116.33 mm (4.5799 in)
Standard valve stem diameter	IN: 6.470-6.485 mm (0.2548-0.2550 in) EX: 5.460-5.480 mm (0.2149-0.2157 in)
Minimum valve stem diameter	IN: 5.424 mm (0.2135 in) EX: 5.419 mm (0.2133 in)
Standard valve guide inner diameter	IN: 5.510-5.530 mm (0.2170-0.2177 in) EX: 5.510-5.530 mm (0.2170-0.2177 in)
Standard clearance between valve stem and guide	IN: 0.010-0.060 mm (0.0004-0.0024 in) EX: 0.010-0.065 mm (0.0004-0.0026 in)
Maximum clearance between valve stem and guide	0.10 mm (0.0039 in)
Standard valve guide projection height	IN: 16.4-17.0 mm (0.646-0.669 in) EX: 16.4-17.0 mm (0.646-0.669 in)
Valve spring installation height	IN: When pressurized with spring force of 130-210 N (13.0-21.4 kgf, 28.7-47.2 lbf), spring height is 30.0 mm (1.181 in). EX: When pressurized with spring force of 228-262 N (23.5-26.6 kgf, 53.3-58.6 lbf), spring height is 33.0 mm (1.299 in). IN: 31.1 mm (1.224 in) EX: 31.1 mm (1.224 in)

[Download PDF version of :](#)
Mazda 5 Workshop Manual